

FICHE TECHNIQUE

Référence : ADP325A

Désignation : Pastille adhésive transparente

Technical Information

Product Code 9389 Peelable Discs

Face Material

Gloss clear polypropylene film, top coated for printability.

Type	Top coated polypropylene
Colour and Finish	Gloss Clear
Weight	54 g/m ² ±10% ISO 536
Thickness	60 µ ±10% ISO 534

Adhesive

Acrylic removeable adhesive featuring high clarity and clean removal from glass, laminated plastics and crosslinked enamels.

Reference	AR801
Type	Acrylic removeable
Min. Appl. Temp.	+5°C
Service Temp.	-40°C/+120°C
Shear	High
Tack	2 N/inch ² FINAT FTM9
Final Adhesion	2 N/inch FINAT FTM2
This adhesive complies with FDA 175.105.	

Liner

Type	1 side siliconised glassine
Colour and Finish	Yellow
Weight	62 g/m ² ±10% ISO 536
Thickness	55 µ ±10% ISO 534
Transparency	...50 % ±10% DIN 53 147-64

Shelf life

12 months, applicable only to the material delivered by Convertex which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- ☐ This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- ☐ Storage area must be dry and clean.
- ☐ Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- ☐ Do not expose to direct sunlight or heat sources.

Unless otherwise indicated, the figures above are average values and should not be treated at face value for specification purposes. The Company reserves the right to improve products, and any change in specification will result in a re-issue of the information sheet. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modification or otherwise. Please check that you have the latest issue of the information sheet. All slitting and length tolerances are to British Standards, but other tolerances are available by request.