

Pastille de fermeture – Adhésivité forte

Face Material

Gloss clear polypropylene film, top coated for printability.

Type	Top coated polypropylene	
Colour and Finish	Gloss Clear	
Weight	45 g/m ² ±10%	(ISO 536)
Thickness	50 µ ±10%	(ISO 534)

Adhesive

Acrylic permanent adhesive featuring high clarity and cohesion, with strong adhesion to apolar substrates (like PE and PP).

Reference	AP901
Type	Acrylic permanent
Min. Appl. Temp	-5°C
Service Temp.	-40°C/+120°C
Shear	High
Tack	8 N/inch ² FINAT FTM9
Final Adhesion	7 N/inch FINAT FTM2

This adhesive is approved by ISEGA, (direct contact dry and moist, non fatty foodstuffs), according to the German Recommendations XIV, and complies with FDA 175.105.

Liner

Type	1 side siliconised glassine	
Colour and Finish	White	
Weight	62 g/m ² ±10%	(ISO 536)
Thickness	55 µ ±10%	(ISO 534)
Transparency	45 % ±10%	(DIN 53 147-64)

Shelf life

12 months, applicable only to the material delivered by Fantastak Ltd which has not undergone further processing,
under the following STORAGE CONDITIONS:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.